





- Roof fan with square connection.
- Horizontal outlet.
- High performance and proven reliability.
- Operational in both 50 and 60 Hz.
- Impeller with backward curved blades.
- The external rotor motor has maintenance-free sealed ball-bearings.
- Integrated motor protection.
- Junction box has enclosure class IP 54.
- For speed control a transformer or electronic speed controller can be connected.
- Fan housing is manufactured from galvanized sheet steel which is polyester plastic coated in black as standard.
- Swing-up design to simplify maintenance and cleaning of the impeller.
- The easiest way to mount the roof fan is with a roof curb, TFU to TKS.
- The fan complies with environmental requirement M2.
- To comply with the ErP 2018 regulation, a local demand controller must be used.


PRESSURE/FLOW



POWER/FLOW



SFP



TECHNICAL DATA

Voltage	230 V
Frequency	50 Hz (60 Hz)
Phase	1 ~
Current	0.20 A
Power	49 W
Speed	2250 r.p.m.
Max. temp of transported air	80 °C
Sound pressure level, 3 m	55 dB(A)
Weight	4.3 kg
Enclosure class	44 IP
Wiring diagram	4040002

SOUND DATA

	L_{wa} tot dB (A)	63	125	250	500	1K	2K	4K	8K
Surrounding 230 V	62	48	38	50	54	59	56	48	39
Inlet 230 V	61	42	50	57	55	54	52	44	31

Available in following design:

Black	7210009
Brick red	7210029

MORE INFORMATION



Find out the latest updated information about this product by visiting www.ostberg.com or scanning this QR code.

ACCESSORIES

- Roof curb TFU 300
- Connection plate TFU 300
- Back draught shutter TFU 300
- Transformer controller VRTE C
- Transformer controller VRDE 1.5
- Speed controller VRS 0.5
- Local Demand Controller Kit

DIMENSIONS (mm)

