





- Roof fan with square connection.
- Vertical outlet.
- High performance and proven reliability.
- Impeller with backward curved blades.
- The external rotor motor has maintenance-free sealed ball-bearings and is very energy efficient.
- Speed controlling can be done with the built-in potentiometer, 0-10 V alt. external control.
- Integrated motor protection.
- Junction box has enclosure class IP 54.
- Fan housing is manufactured from galvanized sheet steel and is polyester plastic coated. Can be ordered uncoated or with coating that complies with the Environmental class M3/Corrosion class C4.
- Swing-up design to simplify maintenance and cleaning of the impeller.
- The easiest way to mount the roof fan is with a roof curb TFU.


PRESSURE/FLOW



POWER/FLOW



SFP



TECHNICAL DATA

Voltage	230 V
Frequency	50/60 Hz
Phase	1 ~
Current	3.75 A
Power	855 W
Speed	2210 r.p.m.
Max. temp of transported air	60 °C
Sound pressure level, 3 m	79 dB(A)
Weight	30.2 kg
Enclosure class	54 IP
Wiring diagram	4040145

SOUND DATA

	L_{wa} tot dB (A)	63	125	250	500	1K	2K	4K	8K
Surrounding 10 V	86	52	63	77	79	82	80	75	69
Inlet 10 V	85	63	69	80	80	77	74	73	68
Inlet 8.5 V	82	61	68	77	76	73	70	68	73
Inlet 7 V	77	57	67	69	70	66	64	62	72
Inlet 5 V	68	52	59	60	61	56	55	62	60

Available in following design:

Black C4	7351041
Galvanized	7351001

MORE INFORMATION



Find out the latest updated information about this product by visiting www.ostberg.com or scanning this QR code.

ACCESSORIES

- Roof curb TFU 560
- Connection plate TFU 560
- Back draught shutter TFU 560
- Controller IQ-Reg EC
- Speed controller MS EC
- Pressure regulator CALAIR-PR-230V
- Pressure regulator FKP-R

DIMENSIONS (mm)

(mm)

